



## Tadiran Tad3G

### Entry Level IP Phone

Tadiran's Tad3G is an entry level Gigabit color screen SIP phone with high performance specially for enterprise. It features a 2.4-inch 320x240 pixel color screen and local 6-party conferencing to render a user-friendly experience. Tad3G has rich functions such as HD audio, dual 10/100/1000 Mbps network ports and integrated PoE, providing an efficient and high-quality business communication experience for enterprises.

#### Highlights:

- 2.4-inch 320x240 pixel color screen
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Support EHS wireless headset
- Dual 10/100/1000 Mbps network ports, integrated PoE
- Two installation methods of desktop stand and wall mountable

#### Phone Functions

- Local Phonebook (1000 entries)
- Remote Phonebook (LDAP, 1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Plantronics wireless headset(Through Plantronics APD-80 EHS Cable)
- Support Jabra wireless headset(Through EHS20 EHS Cable)
- Support Recording (Through Server)
- Action URL / Active URI

#### Generic

- HD Voice
- PoE Enabled
- 2.4-inch color screen
- Handset / Hands-free / Headset mode
- Desktop Stand / Wall mountable( optional)
- Optional External Power Supply

#### Call Functions

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 6-party Conference
- Hot Line
- Hot desking
- Enhanced SIP Functionality (ROD, Camp on busy, ULA)

## Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

## Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- LLDP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

## Audio

- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

## Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog



## Physical Specifications

- LCD: 2.4-inch (320x240) Color Screen
- Keypad: 36 keys, including:
  - 4 Soft-keys
  - 9 Function keys (Hold/Transfer/Voice message/Conference/Phonebook/MWI/Headset/Redial/ Hands-free)
  - 3 Line keys (With LED Indicator Light)
  - 4 Navigation keys
  - 1 OK key
  - 12 Standard Phone Digits keys
  - 3 Volume Control keys (Up/Down/Mute (Microphone))
- Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT.5E Ethernet Cable x1
- Desktop Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- DC Power Input: DC5V / 0.6A
- Power Consumption(Adapter): 0.84 ~1.43W
- Power Consumption(PoE): 1.32 ~2.09W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation:
  - Desktop Stand
  - Wall mountable( optional)
- Color: Black
- N.W/CTN: 8.55kg
- G.W/CTN: 9.26kg
- Device Dimensions:
  - Desktop Stand (45°): 169x203.6x172.7 mm
  - Desktop Stand (50°): 169x194x181 mm
  - Wall mountable: 169x113.4x207.6 mm
- Outer CTN Dimensions: 460x300x270mm(10 PCS)

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), ContactCenter, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, UCaaS, Contact Centers, Dispatch Console, IP phones and mobility and desktop solutions.

Copyright © 2023 TadiranTelecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.